










Tool Mounting Unit

TUT-15 : Pressure 5-15kg
TUT-30 : Pressure 15-30kg

Weight approx. 6kg



Tool List

Mounting Unit	Use the tool mounting unit depending on the material to be processed. TUT-15 : OPT-C0250 or TUT-30 : OPT-C0271 Included in each CFX package								For TUT-30
Tool Name	Electric reciprocating tools E12	Electric reciprocating tools E35	Electric reciprocating tools E60	V-cut tool V45 Type-S	V-cut tool VAS Type-S	Flat blade tool FBT	Creasing tools 16mm C16	Creasing tools 26mm C26	Creasing tools 60mm C60
Item codes	OPT-C0272	OPT-C0257	OPT-C0258	OPT-C0277	OPT-C0278	OPT-C0256	OPT-C0261	OPT-C0262	OPT-C0263
Tool Shape									
Max. material thickness	54mm	54mm	54mm	20mm	20mm	T04 holder : 4.0mm T06 holder : 6.0mm (Holder included with tool)	2mm	5mm	10mm
Weight	2.4kg	2.2kg	2.2kg	0.6kg	0.5kg	0.3kg	0.4kg	0.4kg	0.4kg
Features	Amplitude 1.2mm / Rotation speed 12000rpm, cuts foam board and other surfaces cleanly	Amplitude 3.5mm / Rotation speed 5500rpm Cuts honeycomb boards cleanly	Amplitude 6.0mm / Rotation speed 5500rpm, Newly designed blade enables cutting of thick sponges	Used for V-cut with 45 degree angle	Variable angles in 5 positions without the use of special tools 0/15/22.5/30/45 degrees	Easy detachment of blades	Roller shaped tool for creasing thin coated balls	Roller shaped tool for creasing A type corrugated cardboard and polypropylene	Roller shaped tool for creasing AA and AB corrugated cardboard
Primary Supported Materials	Foam board Honeycomb board AAA, AA, AB Carrugated cardboard	Honeycomb board AAA, AA, AB Currugated cardboard	Sponge or other cushioning material	Honeycomb board AAA Currugated cardboard	Honeycomb board AAA Currugated cardboard	Coated cardboard Coated polypropylene A, B, E Currugated cardboard	Coated cardboard B, E Currugated cardboard	Coated polypropylene A Currugated cardboard	AAA, AA, AB Currugated cardboard